

Hydraulic Groups - HB-116

Fully brass hydraulic group with front pump connection, designed for combi type heating devices.

By-pass function is carried out via external copper pipe.

Compatible with all circulation pump make and models, and suitable to be used with on off and stepper type 3WV actuators.


Standard content of delivery includes flow and return blocks with DHW filter, flow regulator as per customer request, radial type turbine flow meter with Hall effect sensor, manual filling tap, 3WV cartridge, brass or plastic 3 bar 1/2" pressure relief valve, 1/2" and 3/4" brass connection nipples.

The hydraulic set could be customized and provided with a plate heat exchanger, 3WV motor, pressure switch or sensor and NTC sensor upon customer request.

Constructive Properties

Flow Detection	· Turbine Type Flowmeter with Hall Effect Sensor
Pump Connection	· Front
By-Pass Type	· External - Through copper tube
Material	· CuZn40Pb2 (CW617N)
Flow Regulator	· 6 to 22 (lt/min)
Pressure Relief Valve	· 3 bar 1/2"

Technical Drawings - HB-116



- 1 DHW Filter
- 2 Flow Regulator
- 3 Flow Sensor
- 4 Filling Tap
- 5 Circulation Pump
- 6 Expansion Vessel Connection
- 7 Safety Valve
- 8 External Bypass
- 9 3 Way Valve Motor
- 10 Pressure Switch Sensor Connection
- 11 3 Way Valve
- 12 Plate Heat Exchanger

- A Heating Delivery CH
- B Sanitary Water Outlet DW
- C Sanitary Water Inlet DW
- D Heating Return CH

