



Pressure Gauges - MC 160

- Capsule diaphragm gauges are used to measure low pressure values
 - Do not use if high viscosity fluids or crystallisable form available
 - Used with gas and liquids which do not attack stainless steel 316L.
 - In vibrating environments or with pulsating pressures liquid filled types should be use
- Industry Sector: Medical devices, Gas, Energy lines, and Machinery Manufacturing





Usage Properties

Operating Pressure (max.)	· Must not exceed %75' of full scale.
Conformity	· EN 837 - 3
Accuracy Class	· CL 1.6
Ambient Temperature	· - 20 ... + 60 °C
Protection Rate	· IP 41
Mechanical Vibration Test	· 10Hz-150Hz 1 Octave/minute - 3 axis
Mechanical Shock Test Load	· 15g
Optimum Operating Range	· Between 0,1 x PN and 0,75 x PN
Over Pressure Limit	· PN x 1.25
Fluid Temperature	· Maximum + 100 °C
Storage Temperature	· -40 ... +70 °C



Constructive Properties

Mounting Type	· Bottom Connection
Scale Unit	· mbar
Scale Range (PN)	· 0/25 · 0/40 · 0/60 · 0/100 · 0/160 · 0/250 · 0 - 315 · 0/400 · 0/600 · 0 - 1000
Vacuum Scale Range	· -1000 / 0 · -16 / 0 · -25 / 0 · -40 / 0 · -60 / 0 · -100 / 0 · -160 / 0 · -250 / 0 · -400 / 0 · -600 / 0
Case	· Stainless Steel AISI-304
Bezel	· Stainless Steel AISI-304
Movement	· Stainless Steel AISI-304
Window	· Safety Glass
Wetted Parts	· Stainless Steel AISI-316L
Connection	· G 1/2" B
Dial	· Aluminum
Pointer	· Aluminum
Welding	· TIG Welding



Technical Drawings - MC 160



160 13 103 /



160 13 101 /



160 13 102 /