



Pressure Accessories - Cooling Tower

Cooling tower is mounted between pressure gauge and diaphragm for measuring high temperature mediums.

Usage Properties


| Operating Pressure (max.) | · 600 bar |
|---------------------------|--|
| Operating Temperature | · -40/+150°C |
| Storage Temperature | · -40 +70 °C |
| Applications | \cdot If the medium is aggressive, all stainless steel types should be used. |

Constructive Properties

| Mounting Type | · Vertical |
|--------------------|-----------------------------|
| Case | · Stainless Steel AISI-316L |
| Inlet Connections | · G 1/2" |
| Outlet Connections | · G 1/2" |



Technical Drawings - Cooling Tower



| Model# | Malzeme | d | L | Ι |
|---------------|-------------------------------|--------|-----|----|
| 1051 04 03 02 | 051 04 03 02 AISI 316L G 3/8" | | 98 | 19 |
| 1051 04 03 01 | Pirinç | G 3/0 | 90 | 19 |
| 1051 04 02 02 | AISI 316L | G 1/4" | 94 | 15 |
| 1051 04 02 01 | Pirinç | 6 1/4 | | |
| 1051 04 04 02 | AISI 316L | G 1/2" | 102 | 23 |
| 1051 04 04 01 | Pirinç | 0 1/2 | | |

1051 04 /